



FLORY **FIELD** **ELEVATORS**

4840 AND 4890



FLORY INDUSTRIES

GOFLORY.COM

> (209) 545-1167

> 4737 Toomes Rd, Salida Ca 95368

FLORY 4840 AND 4890


FIELD ELEVATORS

FEATURES

- High capacity 48 in. wide belt with variable speed, minimizes unload time, which maximizes shuttle efficiency
- Automatic engine speed and belt start actuated by shuttle trigger
- Powered drive wheel allows for easy movement and positioning
- Adjustable output hood centers the load in the trailer without repositioning
- Large unload area and smooth transition from the shuttle prevents loss and damage to the product
- The 180° swivel on the 4890 is actuated by a simple hydraulic cylinder and linkage with maintenance-free bushings, which results in smooth motion and ease of service
- Wireless remotes allow control of elevator functions by the ground crew or directly from the cab of the shuttle
- Trough mounted E-stop, work lights and flashing light tower enhances operator safety
- Suspension axle, integrated brakes and LED lighting improves towing safety
- Cyclone hydraulic tank technology, reduces oil requirement by 25 gallons

OPTIONS

- Adjustable output hood (standard on 4890)
- Cleated belt
- Cover tarp (to prevent bounce-out)



WIRELESS REMOTE






SPECIFICATIONS

ENGINE	CAT, 3.6 L, TIER 4F
HORSEPOWER	74 HP
FUEL TYPE	DIESEL #2, ULTRA LOW SULFUR
FUEL CAPACITY	37 GAL.
NO DEF REQ.	
HYD. OIL CAPACITY	12 GAL.
BELT WIDTH	48 IN.
REAR TIRES	235 - 75R - 17.5, 18 PLY
4840 DRIVE	18 X 7.00 - 8, 16 PLY
4890 DRIVE	26 X 12.00 - 12, 10 PLY
4840 WEIGHT	8,940 LBS.
4890 WEIGHT	11,620 LBS.



TRANSPORT POSITION





FLORY INDUSTRIES

GOFLORY.COM > (209) 545-1167 > 4737 Toomes Rd, Salida Ca 95368

V1